| | Net Speaker | Net Speaker Lite |
|---|---|---|
| | 2N" Netspeaker 2N" Netspeaker (Audio system) Wohene Channel adjustment Left mattre LID | And Micro SD Wohmer Channel adjustment When Special System Handphones (Line out Micro SD R. Sensor Informative LED |
| Channels | 4 | 4 |
| Playout of prerecorded message on input | V | ٧ |
| Autonomous/server operation available | ٧ | ٧ |
| Offline mode | V | ٧ |
| Audio back-up (microSD card) | ٧ | √ |
| SIP phone function | × | × |
| VoIP trunk | √ | √ |
| Web server | × | × |
| Telnet | √ | ٧ |
| IP paging | √ | ٧ |
| Audio codecs | MP3 stereo up to 320kbit 44.1kHz 16bit / SIP on G.711, RTP multicast G711 or L16 | MP3 stereo up to 320kbit 44.1kHz 16bit / SIP on G.711, RTP multicast G711 or L16 |
| Playout system | √ | √ |
| Priorities | ٧ | ٧ |
| Scheduler of tracks to be played | √ | √ |
| Zone definition | √ | ٧ |
| Internet radio support | √ | ٧ |
| Remote monitoring | √ | ٧ |
| SIP alerting | × | × |
| Mobile devices applications | √ | √ |
| Powered by PoE | √ | × |
| Power amplifier | ٧ | × |